(12) 按照专利合作条约所公布的国际申请

(19) 世界知识产权组织
国 际 局

(43) 国际公布日:
2005年9月15日(15.09.2005)

PCT

(10) 国际公布号:
WO 2005/086510 A1

(51) 国际分类号[7]: H04Q 7/30

(21) 国际申请号: PCT/CN2004/000179

(22) 国际申请日: 2004年3月5日(05.03.2004)

(25) 申请语言: 中文

(26) 公布语言: 中文

(71) 申请人(对除美国以外的所有指定国): UT 斯达康通讯有限公司(UTSTARCOM TELECOM CO., LTD) [CN/CN]; 中国浙江省杭州市文一路129号益乐工业园2-3号楼, Zhejiang 310012 (CN).

(72) 发明人;及
(75) 发明人/申请人(仅对美国): 刘晟(LIU, Sheng) [CN/CN]; 赵柏骏(ZHAO, Baijun) [CN/CN]; 黄小庆(HUANG, Bill) [US/CN]; 中国广东省深圳市南山区高新技术产业园联恩大厦3层, Guangdong 518057 (CN).

(74) 代理人: 中国国际贸易促进委员会专利商标事务所(CCPIT PATENT AND TRADEMARK LAW OFFICE); 中国北京市阜成门外大街2号万通新世界广场8层, Beijing 100037 (CN).

(81) 指定国(除另有指明, 要求每一种可提供的国家保护): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW

(84) 指定国(除另有指明, 要求每一种可提供的地区保护): ARIPO(BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), 欧亚专利(AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), 欧洲专利(AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI(BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

本国际公布:
— 包括国际检索报告.

所引用双字母代码和其它缩写符号, 请参考刊登在每期PCT公报期刊起始的"代码及缩写符号简要说明".

(54) Title: TRANSMISSION OPTIMIZING BASED ON LOAD-SHARE IN RADIO BASE STATION SYSTEM

(54) 发明名称: 基于负荷分担的无线基站系统中的传输优化



1 COMBINE
2 ANTENNA UNIT
3 GROUP-BROADCAST/BROADCAST

(57) Abstract: Providing a method of signal transmission, the method includes: in downward, sending the downward data frame of the cell by the radio network control equipment to the base station which concerns of its channel process so as to perform process; the first base station receive the downward radio signal from the base station which the channel of downward data frame of the cell concerns of; and the first base station transmits radio signal to the cell; in upward, the first base station receive the upward radio signal of the cell; the first base station distribute the upward radio signal to the base station which its channel concerned of so as to perform process; the radio network control equipment receive the corresponding upward data frame from the base station which the channel process of the upward radio signal concerned of , the base station which the downward data frame channel process or the upward radio signal concerned of include at least the second base station .

[见续页]

WO 2005/086510 A1